

TreuVaz Series

TV-5025-SE

Point-to-Point Radio

PRODUCT DESCRIPTION:

TV-5025-SE is a carrier-class radio that belongs to the TreuVaz 5025 Series and supports 5.7 to 5.8 GHz frequency range.

The Radio complies with Universal, FCC IC, MII & WPC regulations with a factory default of 5.8 GHz FCC IC.

TV-5025-SE delivers up to 25 Mbps throughput and up to 4xE1s / T1s over an extended range.

The radio is connectorized for external antenna (2 x N-type).



PRODUCT HIGHLIGHTS :

- 25 Mbps Ethernet net throughput and 4xE1s / T1s Native TDM interfaces
- Long range - Up to 120 km / 75 miles
- Telco-grade, extremely robust in harsh conditions
- Supports intra-site and inter-site synchronization to maximize capacity
- Adaptive asymmetric throughput – dynamic allocation between uplink and downlink
- Advanced OFDM & MIMO technologies for operation in nLOS NLOS and dense radio environments



Treunetz is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at <http://www.treunetz.at/> for the most up-to-date specifications and contact information.

PRODUCT SPECIFICATIONS:

Configuration					
Architecture	Outdoor Unit connectorized for external antenna (2 x N type)				
PoE to ODU Interface	Outdoor CAT-5e Maximum cable length: 100m for 10/100BaseT				
Radio					
Max Capacity	25 Mbps net aggregate throughput (up to 4xE1s/T1s plus Ethernet)				
Range	Up to 120 km / 75 miles				
Channel Bandwidth	Configurable: 5, 10, 20 MHz (for the default band)				
Modulation	2x2 MIMO-OFDM (BPSK/QPSK/16QAM/64QAM)				
Adaptive Modulation & Coding	Supported				
Automatic Channel Selection	Supported				
DFS	Supported (FCC IC)				
Diversity	Supported				
Spectrum Viewer	Supported				
Max Tx Power	25 dBm				
Duplex Technology	TDD				
Error Correction	FEC k = 1/2, 2/3, 3/4, 5/				
Encryption	AES 128; FIPS 197				
Support Indoor units	IDUs: TreuRack (RackMount IDU) TreuDop (Desktop IDU) TreuPoz (POE Devices) TP-601X-U Series				
Uplink Downlink Allocation	Configurable: Symmetric or Asymmetric				
QoS	Packet classification to 4 priority queues according to 802.1P or Diffserv				
VLAN Support	802.1Q, QinQ, 4094 VLANs				
Ethernet Ring Protection	Supported including Ethernet 1+1				
TDD Intra Site Synchronization	Supported				
TDD Inter Site Synchronization	Supported				
Monitored Hot Standby	1+1 with Treunetz Point-to-Point Radio				
Supported Bands					
Band	Channel BW 5MHz [GHz]	Channel BW 10MHz [GHz]	Channel BW 20MHz [GHz]	Channel BW 40MHz [GHz]	Radio Compliance
5.8 GHz FCC IC (default)	5.7275-5.8475	5.725-5.850	5.725-5.850		FCC 47CFR Part 15.247; IC RSS-210
Power					
Power Feeding	Power provided over ODU-IDU cable				
Power Consumption	<12 W				
Environmental					
Operating Temperatures	-35°C to 60°C / -31°F to 140°F				
Humidity	100% condensing, IP67 (totally protected against dust and against immersion up to 1m)				
Safety					
FCC IC (cTUVus)	UL 60950-1, UL 60950-22, CAN/CSA C22.2 60950-1, CAN/CSA C22.2 60950-22				
ETSI	EN/IEC 60950-1, EN/IEC 60950-22				
EMC					
FCC	47 CFR Class B, Part15, Subpart B				
ETSI	EN 300 386, EN 301 489-1, EN 301 489-4				
CAN/CSA-CEI/IEC	CISPR 22-04 Class B				

ORDERING INFO:

Part Number: TV-5025-SE

Description: TreuNetz - TreuVaz 5025 Series ODU , connectorized for external antenna (2 x N-type), factory default 5.8 GHz FCC/IC

